


PROFESSIONAL STARTERcable 1200A



Up to 1200A peak amps

For transferring the charging current to start even almost completely discharged batteries



Up to 9.5 liter

Suitable for starting vehicles with a petrol or diesel engine with a capacity of up to 9.5L



600A Continuous amp rating

For permanent current transmission and protection against overheating, a continuous amp rating of 600A is given



Pure Copper

The cable consists of multi-stranded conductors made of pure copper



Professional starter cables from OSRAM

With a range of OSRAM starter cables, motorcycle, car, commercial vehicle and truck drivers now have a quick and easy solution to rapidly transfer the battery power between a donor and a receiver vehicle and thus become ready to drive again. The OSRAM BATTERYstart PROFESSIONAL STARTER CABLE 1200A is a high quality starter cable designed for professional and private use. The cables consist of multi-stranded conductors made of pure copper, which makes the resistance of the cable extremely low and enables a constant and effective transmission of the charge. The starter cable has a length of 5 meters with a cross-sectional area of 50mm². Thanks to the length and the cross-sectional area, it is possible to start vehicles with petrol and diesel engines with up to 9.5 liters of displacement, as a peak current strength of up to 1200A can be achieved, at the same time a continuous amp rating of 600A is given. It is suitable for voltages of 12V and 24V. To prevent high wear and tear, the OSRAM BATTERYstart STARTER CABLE 1200A is sheathed in flexible yet durable PVC, the insulated clamps and handles provide additional safety and durability. The different colors of the cables and the handles on the clamps reduce the risk of mixing up the positive and negative terminals and thus the risk of incorrect connection to the battery. The storage bag included in the scope of delivery allows the cables to be stored tidy and, in a space-saving manner. Conveniently, the operating instructions are also attached to the back of the storage bag and are thus quickly at hand. OSRAM offers a 2-year guarantee* on this product.

Technický list výrobku

Technické údaje


Informace o produktu

Engine type	Diesel / Petrol
-------------	-----------------

Parametry

Špičkový proud	1200A
Continuous amp rating	600 A

Rozměry & váha



Délka	345 mm
Šířka	280 mm
Výška	100,0 mm
Dálka vodiče	5,0m
Cross section area	50 mm ²
Engine size	≤ 9.5L

Barvy & materiály

Materiál	Copper
----------	--------

Logistické údaje

Kód výrobku	Popis výrobku	Jednotka balení (kusy/jednotku)	Rozměry (délka x šířka x výška)	Objem	Hrubá hmotnost
4062172221016	STARTERcable 1200A	Bag 1	340 mm x 340 mm x 100 mm	11.56 dm ³	13234.00 g
4062172221023	STARTERcable 1200A	Shipping carton box 2	360 mm x 200 mm x 300 mm	21.60 dm ³	13626.00 g

Zmíněný produktový kód udává nejmenší jednotku množství, kterou lze objednat. Jednotka balení může obsahovat jeden nebo více samostatných produktů. Při objednávání zadávejte jednotky balení nebo násobky jednotek balení.

Technický list výrobku

Právní rady

* přesné podmínky najdete na:

www.osram.cz/am

Application advice: For more detailed application information and graphics please see product datasheet and user manual.

Pokyny k použití

Podrobnější informace k použití a grafiku najdete v technickém listu.

Vyloučení odpovědnosti

Změny bez předchozího upozornění vyhrazeny. Chyby a opomenutí vyhrazeny. Vždy se ujistěte, že používáte nejnovější vydání.

OSRAM